

Smooth dimming experience that parallels traditional incandescent and halogen lamps.



Dimming with Ordinary Dimmer Switch

1. Switch the lamp ON for at least 1 minute until it reaches 100% brightness level.*
2. To dim, turn the knob at anti-clockwise direction to achieve desired brightness level.

100%

Smooth Dimming

10%



Notes:

The DIMMERABLE lamps are compatible with most electronic dimmers and digital dimmers for incandescent and halogen lamps. Touch dimmers and Remote-controlled dimmers do not apply.

For best dimming results, the wattage of the DIMMERABLE lamp should not fall below 1/6th the wattage of the MINIMUM load. Conversely, the lamps should not exceed the MAXIMUM load of the dimmer switch.

Malfunction or failure of the dimmer switch may occur if the total wattage of the DIMMERABLE lamps exceeds the maximum wattage load of the dimmer switch itself.



CL809d

Lamp Base	Diameter (mm)	Length (mm)	Weight (g)
E27	43	118	63
E14	43	123	63

9 Watt | 10,000 hours | 405lm | Standard Pack 60 (10)



GSU111d

Lamp Base	Diameter (mm)	Length (mm)	Weight (g)
E27	60	114	76

11 Watt | 10,000 hours | 570lm | Standard Pack 60 (10)







GSU418d

Lamp Base	Diameter (mm)	Length (mm)	Weight (g)
E27	98	149	174

18 Watt | 10,000 hours | 1008lm | Standard Pack 24 (6)



Remarks: Opal glass cover



DIMMERABLE



100% - 10% Brightness

ENERGY SAVING LAMPS



SLU111d

Lamp Base	Diagonal (mm)	Length (mm)	Weight (g)
E27	42	106	51
E14	42	113	50

11 Watt 10,000 hours **600lm** Standard Pack 60 (10)



3U218d

Lamp Base	Diameter (mm)	Length (mm)	Weight (g)
E27	49	138	89

18 Watt 10,000 hours **1008lm** Standard Pack 24 (6)



BR1411d

Lamp Base	Diameter (mm)	Length (mm)	Weight (g)
GU10	50	76	64

11 Watt 10,000 hours Beam Angle **119°** Standard Pack 60 (10) Operating Temperature +40°C -10°C



Dimming with Ordinary Dimmer Switch

1. Switch the lamp ON for at least 1 minute until it reaches 100% brightness level.
2. To dim, turn the knob at anti-clockwise direction to achieve desired brightness level.

100%

Smooth Dimming

10%

